

CHROMOJET tabletop printer





DIGITAL FUNCTIONALIZATION & PRINTING APPLICATIONS

- CHROMOJET tabletop printer is perfect to develop new applications, processes and recipes in the field of CHROMOJET pile product printing and digital functionalization using valve jet technology
- results can be transferred to the CHROMOJET production printer
- small removable medium tanks provide quick and easy change of fluids and dyes
- designs and patterns can be uploaded from a normal computer
- resolution, rasterization, pressure, head-speed, nozzle size, viscosity: these are the parameters to control penetration, pick-up and definition
- needs very little space on a table.



SCOPE OF SUPPLY

- control system with:
 USB Interface
 print software
 connecting cable
- 4 modules with 8 jets each
- nozzle sizes:
 100 | 120 | 150 | 200 | 250 | 280 μm
- 4 tanks 300 ml, 1 tank 1,300 ml



VARIABLES EFFECTING THE PICK-UP

The pick-up is influenced by the following variables: viscosity, pressure, head-speed, coverage, nozzle diameter, thickener behavior

Considering all possible variables the pick-up can result in a range of 1:500!

OPTIONS AND SPARE PARTS

- jet modules with 100 | 120 | 150 | 200 | 250 | 280 μm
- filter-kit with 10 additional filters
- tanks with 0.3, 0.6 and 1.3 liters

APPLICATIONS

Development and testing of print recipes for CHROMOJET print applications

- digital functionalization tests with up to 4 chemicals
- print tests on various substrates





110/230 Volt | 50/60 Hz

air supply: 4 bar

sample size: max. 300 x 300 mm

number of colors / tanks / modules:

1-4 modules

iets:

8 jets per module

nozzle diameters available:

100 | 120 | 150 | 200 | 250 | 280 μm

head speed:

0.3 - 1 m/sec

medium pressure:

1.0 - 3.5 bar

medium viscosity:

0 - 500 cps

filters:

 $25 \, \mu m$ filter for each module





ZIMMER MASCHINENBAU GMBHDIGITAL PRINTING SYSTEMS







Your competent partner for process development, engineering, manufacturing and implementation of industrial printing and coating systems.